



SAFEX™ Trailer Power

AUTO SAFE: All Versions

The SAFEX system allows fleets to safely and easily connect their vehicles to 480/240/208 VAC power while at the dock (meeting CARB and other environmental regulations).

The Auto Safe is designed to protect personnel from electric shock while providing 480/240/208 volt shore power to a vehicle. Whenever the plug is removed from the socket, the Auto Safe automatically disconnects the power, ensuring safe interaction with the cable at all times.



Specifications:

Input.....	480/240/208 VAC, 50/60 Hz, 3 phase	Temperature range	-20° C to 60° C
Max input amps	30/60/60 amps	Weight	10 lbs
Sensitivity	60 mA	Warranty	3 years

Features:

- Ensures the 480/240/208 volt shore power line is de-energized unless connected to the vehicle
- Applies power only if the plug is connected to the socket and the power button is activated
- De-energizes the plug automatically before the plug is ejected from the vehicle
- Uses a rugged enclosure that meets NEMA and IP67 standards for ultimate outdoor protection
- UL listed
- Easy to install

Product Details:

Description	Part Number	AC Volts	AC Amps	Shipping Weight
Auto Safe	091-129-30-480-10	480	30	7 lbs
Auto Safe	091-129-60-240-10	240	60	10 lbs

Cable Management Spring included in Kit:



Dimensions

